



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: TYFO WP
MSDS NUMBER: WP-A-02

COMPONENT A
DATE: January 8, 2014

PAGE: 1 of 5
SUPERSEDES: 2/04/10

SECTION I: MATERIAL AND MANUFACTURER IDENTIFICATION

MANUFACTURER:
FYFE CO., LLC
8380 Miralani Drive
San Diego, CA 92126

EMERGENCY TELEPHONE NUMBER:
800-424-9300 or 703-527-3887
INFORMATION TELEPHONE NUMBER:
858-642-0694

PRODUCT IDENTIFICATION: TYFO® WP, Component A
CHEMICAL FAMILY: Wet Epoxy Primer

SECTION II: INGREDIENTS

MATERIAL OR COMPONENT	CAS NUMBER	% BY WEIGHT	OSHA(PEL)	ACGIH(TLV)
Proprietary epoxy resin	Proprietary	85-95	Not determined	Not determined
Proprietary component	Proprietary	1-11	Not determined	Not determined

SECTION III: HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

APPEARANCE AND ODOR: Light-yellow, viscous liquid with no distinctive odor.

STATEMENTS OF HAZARD: CAUTION! MAY CAUSE SKIN AND EYE IRRITATION AND SKIN SENSITIZATION.

CONTACT AT ELEVATED TEMPERATURES CAN RESULT IN THERMAL BURNS.

PRIMARY ROUTES OF EXPOSURE:

EYES--NO SKIN CONTACT--YES INHALATION--NO INGESTION--NO

HMIS RATING:

HEALTH--2 FLAMMABILITY--1 REACTIVITY--0 SPECIAL--NONE

POTENTIAL HEALTH EFFECTS:

EYES: Causes irritation to the eyes.

SKIN: Causes moderate skin irritation and sensitization. Contact with product at elevated temperature could cause thermal burns.

INHALATION: Due to low volatility, inhalation is unlikely. Avoid breathing vapor, mist or spray.

INGESTION: Material has a low order of acute oral toxicity, ingestion is unlikely.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Preexisting conditions such as asthma, allergies, eczema and other lung and skin disorders may be aggravated by exposure to the product.

OTHER: The components present in this material at concentrations equal to or greater than 0.1 % are not listed or regulated by IARC, NTP, OSHA or ACGIH as a carcinogen. Dust from machining the cured product may cause mechanical irritation of the eyes, skin, nose, throat and upper respiratory tract.

**EXPOSURE LIMITS FOR CURED
PRODUCT DUST:****OSHA(PEL)**
15 mg/m³(Total)
5 mg/ m³(Respirable)**ACGIH(TLV)**
10 mg/m³
3 mg/m³ (Respirable)**SECTION IV: FIRST AID MEASURES**

EYES: In case of eye contact, immediately flush eyes with large amounts of water for at least 15 minutes, keeping the eyelids open. Get medical attention.

SKIN CONTACT: In case of contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops. Wash contaminated clothing before reuse and destroy contaminated shoes.

INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, qualified personnel may administer oxygen. Get medical attention.

INGESTION: Ingestion of this material is unlikely. If swallowed, get medical attention immediately. Do not induce vomiting.

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT/METHOD OF DETERMINATION: Not determined

MEANS OF EXTINCTION: Use water-spray, foam, dry chemical or CO₂ to extinguish fires. Use water to keep containers cool.

SPECIAL FIRE HAZARDS: Avoid exposure through use of a self-contained, positive-pressure breathing apparatus.

SECTION VI: ACCIDENTAL RELEASE MEASURES

PROCEDURES IN CASE OF ACCIDENTAL RELEASE OF LEAKAGE: Ventilate area. Avoid breathing vapor. Use self-contained breathing apparatus or supplied air for large spills or confined areas. Avoid contact with skin, eyes or clothing (See Section VIII). Contain spill if possible. Absorb or wipe up with suitable material, put into a container and dispose of properly (See Section XIII). Prevent entry into sewers and waterways.

SECTION VII: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place with adequate ventilation. Store in closed containers. Keep sealed from dirt and moisture. Keep away from open flames and high temperatures.

SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Avoid eye and skin contact. Wear chemical type goggles and a face shield.

SKIN PROTECTION: Protective clothing such as uniforms, coveralls or lab coats must be worn. Launder or dry-clean when soiled. Gloves resistant to chemicals are required.

RESPIRATORY PROTECTION: Not ordinarily required. If vapor or mist is generated, use an organic vapor respirator approved by NIOSH, as appropriate. If sufficient dust is generated during machining of the cured product, use a dust respirator approved by NIOSH, as appropriate.

VENTILATION: Local exhaust ventilation recommended sufficient to control the vapor, mist or dust being generated. If exhaust ventilation is not available or is inadequate, use a NIOSH approved respirator, as appropriate.

GENERAL HYGIENE RECOMMENDATIONS: Before eating, drinking, smoking or using toilet facilities, wash face and hands thoroughly with soap and water. If significant amounts of this material gets on work clothes, the employee should shower immediately and the clothing should be laundered before it is worn again.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR	Light-yellow, viscous liquid with no distinctive odor.
BOILING POINT (°F/°C)	Not determined
MELTING POINT (°F/°C)	Not determined
SPECIFIC GRAVITY (WATER = 1)	0.9-1.15
pH OF UNDILUTED PRODUCT	Not determined
VAPOR PRESSURE (mm Hg.)	Not determined
VAPOR DENSITY (AIR-1)	Not determined
VISCOSITY	Not determined
PERCENT (%) VOC	Not determined
SOLUBILITY IN WATER	Not determined

SECTION X: STABILITY AND REACTIVITY

STABILITY: Stable under normal handling and storage conditions. Avoid open flames and high temperatures.

INCOMPATIBLE MATERIALS: Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids and strong mineral and organic bases especially primary and secondary aliphatic amines.

PRODUCTS EVOLVED FROM HEAT OF COMBUSTION OR DECOMPOSITION: The products of combustion and decomposition depend on other materials present in the fire and the actual conditions of the fire. Burning will produce carbon dioxide, carbon monoxide, aldehydes, phenolics, water and other unidentified gases and vapors which may be toxic. Avoid inhalation.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions of use. When mixed with Component B of a resin system and/or rapid heating of the product in bulk may produce an uncontrolled exothermic reaction which may char and decompose the resin system, generating unidentified gases and vapors which may be toxic. Avoid inhalation.

SECTION XI: TOXICOLOGICAL INFORMATION

MATERIAL OR COMPONENT TOXICITY DATA:

MEDIAN LETHAL DOSE (SPECIES):

ORAL (LD ₅₀)	Proprietary epoxy resin	>5,000 mg/kg (Rat)
	Proprietary component	19,200 mg/kg
INHALATION (LD ₅₀)	Proprietary epoxy resin	No deaths in saturated air, 8 hours
	Proprietary epoxy resin	>20,000 mg/kg (Rabbit)
DERMAL (LD ₅₀)	Proprietary component	>4,500 mg/kg, No deaths (Rabbit)

SECTION XI: TOXICOLOGICAL INFORMATION (CONTINUED)

IRRITATION INDEX, ESTIMATION OF IRRITATION (SPECIES):

SKIN	Proprietary epoxy resin	Repeated exposure may cause irritation
	Proprietary component	Moderate irritation (Rabbit)
EYES	Proprietary epoxy resin	Slight temporary irritation
	Proprietary component	Mild irritation
SENSITIZATION	Proprietary epoxy resin	May cause skin sensitization
	Proprietary component	Repeated exposure may cause sensitization

OTHER: None

SECTION XII: ECOLOGICAL INFORMATION**Toxicity**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 h: 2 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Water flea), static test, 48 h, immobilization: 1.8 mg/l

Aquatic Plant Toxicity

ErC50, Scenedesmus capricornutum (fresh water algae), static test, Growth rate inhibition, 72 h: 11 mg/l

Toxicity to Micro-organisms

IC50; Bacteria, 18 h: > 42.6 mg/l

Aquatic Invertebrates Chronic Toxicity Value

Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, NOEC: 0.3 mg/l

Persistence and Degradability

Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Bioaccumulative potential

Bioaccumulation: Bioconcentration potential is moderate

SECTION XIII: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Material for disposal should be placed in appropriate sealed containers to avoid potential human and environmental exposure. It is the responsibility of the generator to comply with all federal, state, provincial and local laws and regulations. We recommend that you contact an appropriate waste disposal contractor and environmental agency for relevant laws and regulations. Under the US, Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets relevant waste classification.

SECTION XIV: TRANSPORTATION INFORMATION**DOT Non-Bulk**

Not regulated

DOT Bulk

Not Regulated

IMDG

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)

Hazard Class: Class 9 ID Number: UN 3082 Packing Group: PG III

EMS Number: F-A, S-F

Marine Pollutant: Yes

ICAO/IATA

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)

Hazard Class: Class 9 ID Number: UN 3082 Packing Group: PG III

Cargo Packing Instruction: 964

Passenger Packing Instruction: 964

Additional Information: Marine Pollutant

SECTION XV: REGULATORY INFORMATION**OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29

CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (chronic) Health Hazard	No
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING ! THE STATE OF CALIFORNIA HAS DETERMINED THAT THE FOLLOWING LISTED MATERIAL OR COMPONENT CHEMICALS IN THIS PRODUCT MAY CAUSE CANCER, BIRTH DEFECTS OF OTHER REPRODUCTIVE HARM: Epichlorohydrin (CAS # 106-89-8), known to cause cancer, trace amount. Phenyl Glycidyl Ether (CAS # 122-60-1), known to cause cancer, trace amount.

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

WHMIS (CANADA): CLASSIFICATION: Class D, Division 2, Subdivision B, Toxic

THIS PRODUCT DOES NOT CONTAIN OR IS NOT MANUFACTURED WITH OZONE DEPLETING SUBSTANCES AS IDENTIFIED IN THE TITLE VI, CLEAN AIR ACT "STRATOSPHERIC OZONE PROTECTION" AND THE REGULATIONS SET FORTH IN 40 CFR, PART 82.

SECTION XVI: OTHER INFORMATION

SPECIAL PRECAUTIONS: Empty containers will retain some of the product residue. When handling or disposing of them, follow all label warnings, other instructions and waste disposal procedures.

EXPLANATION AND DISCLAIMER: Wherever such words or phrases as "hazardous," "toxic," "carcinogen," appear herein, they are used as defined or described under state employee right-to-know laws, Federal OSHA laws or the direct sources for these laws such as the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), etc. The use of such words or phrases should not be taken to mean that we deem or imply any substance or exposure to be toxic, hazardous or otherwise harmful. ANY EXPOSURE CAN ONLY BE UNDERSTOOD WITHIN THE ENTIRE CONTEXT OF ITS OCCURRENCE, WHICH INCLUDES SUCH FACTORS AS THE SUBSTANCE'S CHARACTERISTICS AS DEFINED IN THE MSDS, AMOUNT AND DURATION OF EXPOSURE, OTHER CHEMICALS PRESENT AND PREEXISTING INDIVIDUAL DIFFERENCES IN RESPONSE TO THE EXPOSURE.

The data provided is based on the information received from our raw material suppliers and other sources believed to be reliable. THIS DATA DOES NOT CONSTITUTE A GUARANTEE (EXPRESSED OR IMPLIED), WARRANTY (INCLUDING WARRANTY WITHOUT LIMITATION, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) OR REPRESENTATION (INCLUDING FREEDOM FROM PATENT LIABILITY) BY US WITH RESPECT TO THE DATA, THE PRODUCT DESCRIBED OR ITS USE FOR ANY SPECIFIC PURPOSE, EVEN IF THAT PURPOSE IS KNOWN TO US. WE DISCLAIM LIABILITY FOR DAMAGE OR INJURY INCURRING DIRECTLY OR INDIRECTLY FROM THE USE OF THIS PRODUCT.